

CITY LIGHTS[™] GLASS MOSAIC

wall • countertop • decorative

Vibrancy, radiance, and pure shimmer, that's the new City Lights Collection. Add eye-catching attention to your space and leave the room in a trance with the glow of these glass mosaics. Sixteen new stunning blends inspired by the world's most exciting cities will bring sophisticated excitement to your design. This beautiful collection offers ultimate versatility being used commercially or residentially to create borders, backsplashes, or entire walls. Let your personality shine through the City Lights Collection.

Cover photo features Barcelona $1/2 \times 1/2$ mosaic with Veranda Tones in Zen Garden 6-1/2 \times 20 field tile.





CITY LIGHTS™ GLASS MOSAIC

Mosaic Tile



ST. MORITZ CL65*



HOLLYWOOD CL64*



SOUTH BEACH CL71*



PARIS CL67*



BARCELONA CL66**



ST.THOMAS CL70**

Mosaic Tile



FIJI CL75*



HONOLULU CL72**



LAS VEGAS CL69**



CAPRI CL68**



RIO CL73**



TOKYO CL62*



MONTE CARLO CL63**

BANGKOK CL61**



LONDON CL60**



MANHATTAN CL74**

Backsplash Design Idea



Backsplash features Manhattan 1/2 x 1/2 mosaic with Marble Nouveau Nero 3×6 field tile and 1×12 pencil rail.



CITY LIGHTS™

SIZES

		sq.ft, Carton	PIECES PER CARTON
1/2 × 1/2 Mosaic Blend (12 × 12 Sheet)	- /2" x - /2" (29.21 cm x 29.21 cm)	20.74	22

RESIDENTIAL USAGE



COMMERCIAL USAGE

	INTERIOR		EXTERIOR		
	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL	RESIDENTIAL	Commercial
Floors/Patios	~	✓*			
Walls/Backsplashes	~	~	~	~	~
Countertops	~	~	~	~	~
Pool Decking					
Pool Linings	~	~	~	~	~

Suitable in freezing and non-freezing climates when proper installation methods are followed.

*Office building restroom floors and hotel baths only.

GLASS MOSAIC

TRIM

No trim available

SHADE VARIATION



RANDOM (V4) Extreme color and texture variation from tile to tile and within each tile; a random look.

INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
1/8"	1/16" Approximately

SLIP RESISTANCE (WET) : 2

The higher the rating, the higher the slip resistance.

I <.50	
2 .5059	
3 ≥ .60	

TEST RESULTS

	ASTM#	RESULT
Water Absorption	C373	<0.01%
Breaking Strength	C648	>250 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Coefficient of Friction	C1028	Wet: ≥0.50 Dry: ≥0.70

NOTES

Paper-face and mesh-mounted installation instructions are included in carton.

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions, Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: www.daltile.com/ CommercialFactors

Water, oil, grease etc, create slippery conditions, Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

CITY LIGHTS[™] glass mosaic

wall • countertop • decorative





By their very design, Daltile products can help make it easier for you to earn LEED[™] points and/ or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit daltilegreenworks.com.





